

ROCK CARPET

INSTALLATION

Adhesive bonded

APPLICATIONS

Offices with heavy flow

Computer rooms

Stores

Cinemas and Theatres

Sport Clubs

Libraries

Universities

Schools

Casinos

TECHNICAL DATA SHEET

TOTAL THICKNESS:	5,20mm
ROLL LENGHT:	30ml
ROLL WIDTH:	200cm
FIBER COMPOSITION OF USE SURFACE:	100%PA
BACKING:	100% SYNTHETIC
TOTAL MASS PER UNIT AREA:	1.250 gr/m ²
BODY VOLTAGE:	< 2,0 kV
SOUND ABSORPTION:	20dB
USE INTENSITY LEVEL:	23 - 33
ELECTRICAL BEHAVIOR:	ANTISTATIC
FLAMABILITY (EN 13501-1) :	Bfl-s1

RECOMENDATION

Ideal for use in technical floor systems, as it comes applied in the tile from the factory.



FLEXIBLE



SOUNDPROOFING



ROLL



HEAVY TRAFFIC

Distributed by:  **POLYGROUP**

This company reserves the right to make any changes in their product without prior notice.

Headquarter / Factories: P.I. Navisur c/ Narciso 5-6 41907, Valencina de la Concepción, Seville, Spain. **Phone:** (+34) 955 99 77 31
www.accesfloorpolygroup.com **info@afpolygroup.com**